




# NTNY BEARING LTD

## TYPE TS



## timken I44649 bearing

Bearing No. I44649

Cone Part Number	L44649
Design Units	Imperial
Cage Type	Stamped Steel
C1 - Dynamic Radial Rating (Two-Row, 1 million revolutions) <sup>1</sup>	13900 lbf
C90(2) - Dynamic Radial Rating (Two-Row, 90 million revolutions) <sup>2</sup>	3610 lbf
d	1.0625 in
B - Cone Width	0.5800 in
R - Cone Backface To Clear Radius <sup>3</sup>	0.14 in
da - Cone Frontface Backing Diameter	1.22 in
db - Cone Backface Backing Diameter	1.48 in
Ab - Cage-Cone Frontface Clearance	0.05 in
Aa - Cage-Cone Backface Clearance	0.02 in
a - Effective Center Location <sup>4</sup>	-0.13 in
C90 - Dynamic Radial Rating (90 million revolutions) <sup>5</sup>	2080 lbf
C1 - Dynamic Radial Rating (1 million revolutions) <sup>6</sup>	8010 lbf
C0 - Static Radial Rating	7400 lbf
C <sub>a90</sub> - Dynamic Thrust	1330 lbf

I44649 Bearing 2D drawings and 3D CAD models



## NTNY BEARING LTD

Rating (90 million revolutions) <sup>7</sup>	
K - Factor <sup>8</sup>	1.56
G1 - Heat Generation Factor (Roller-Raceway)	8.9
G2 - Heat Generation Factor (Rib-Roller End)	8.93
Cg - Geometry Factor	0.0526