



NTNY BEARING LTD



6303lu Bearing 2D drawings and 3D CAD models

17,000 mm x 47,000 mm x 14,000 mm ntn
6303lu bearing

Bearing No. 6303lu

Size	17x47x14 mm
Bore Diameter	17,000 mm
Outer Diameter	47,000 mm
Width	14,000 mm
d	17,000 mm
D	47,000 mm
B	14,000 mm
C	14,000 mm
rs min	1 mm
Radial clearance class	CN
Mass	0.12 kg
Dynamic load, C	13.5 kN
Static load, C0	6.55 kN
Fatigue limit load, Cu	0.3 kN
f0	12.2
Nlim (grease)	11,000 rpm
Min operating temperature, Tmin	-25 ° C
Max operating temperature, Tmax	110 ° C
Characteristic cage frequency, FTF	0.36 Hz
Characteristic rolling element frequency, BSF	3.39 Hz
Characteristic outer ring frequency, BPF0	2.54 Hz
Characteristic inner ring	4.46 Hz



NTNY BEARING LTD

frequency, BPFI	
da min	22 mm
da max	25 mm
Da max	42 mm
ra max	1 mm
Category	Single Row Ball Bearings
Inventory	0.0
Manufacturer Name	NTN
Minimum Buy Quantity	N/A
Weight / Kilogram	0.12
EAN	4547359573428
Product Group	B00308
Enclosure	1 Seal
Precision Class	ABEC 1 ISO P0
Maximum Capacity / Filling Slot	No
Rolling Element	Ball Bearing
Snap Ring	No
Internal Special Features	No
Cage Material	Steel
Enclosure Type	Contact Seal
Internal Clearance	C3-Loose
Inch - Metric	Metric
Long Description	17MM Bore; 47MM Outside Diameter; 14MM Outer Race Diameter; 1 Seal; Ball Bearing; ABEC 1 ISO P0; No Filling Slot; No Snap Ring; No Internal Special Features
Category	Single Row Ball Bearing
UNSPSC	31171504
Harmonized Tariff Code	8482.10.50.68
Noun	Bearing



NTNY BEARING LTD

Keyword String	Ball
Manufacturer URL	http://www.ntnamerica.com
Manufacturer Item Number	6303LU
Weight / LBS	0.254
Outside Diameter	1.85 Inch 47 Millimeter
Outer Race Width	0.551 Inch 14 Millimeter
Bore	0.669 Inch 17 Millimeter
bore diameter:	17 mm
static load capacity:	6550 N
outside diameter:	47 mm
precision rating:	ISO Class 0
overall width:	14 mm
finish/coating:	Uncoated
bore type:	Round
bearing material:	High Carbon Chrome Steel
closure type:	Single Seal
cage material:	Steel
row type & fill slot:	Single Row Non-Fill Slot
inner ring width:	14 mm
snap ring included:	Without Snap Ring
outer ring width:	14 mm
internal clearance:	CN
maximum rpm (grease):	11000 rpm
operating temperature range:	-40 to 120 ° C
fillet radius:	1 mm
dynamic load capacity:	13500 N
manufacturer product page:	Click here