



NTNY BEARING LTD



15 mm x 35 mm x 11 mm skf 7202 bep bearing

Bearing No. 7202 bep

7202 bep Bearing 2D drawings and 3D CAD models

Size	35x15x11 mm
Bore Diameter	35 mm
Outer Diameter	15 mm
Width	11 mm
d	15 mm
D	35 mm
B	11 mm
d_1	22.7 mm
d_2	18.93 mm
D_1	27.8 mm
a	16 mm
$r_{1,2}$ - min.	0.6 mm
$r_{3,4}$ - min.	0.3 mm
d_a - min.	19.2 mm
D_a - max.	30.8 mm
D_b - max.	32.6 mm
r_a - max.	0.6 mm
r_b - max.	0.3 mm
Basic dynamic load rating - C	8.3 kN
Basic static load rating - C_0	4.4 kN
Fatigue load limit - P_u	0.183 kN
Reference speed	24000 r/min
Limiting speed	24000 r/min
Calculation factor - k_r	0.095
Calculation factor - k_a	1.4



NTNY BEARING LTD

Calculation factor - e	1.14
Calculation factor - X	0.57
Calculation factor - Y ₀	0.52
Calculation factor - Y ₁	0.55
Calculation factor - Y ₂	0.93
Calculation factor - X	0.35
Calculation factor - Y ₀	0.26
Calculation factor - Y ₁	
Calculation factor - Y ₂	0.57
Category	Angular Contact Ball Bearings
Inventory	2.0
Manufacturer Name	SKF
Minimum Buy Quantity	N/A
Weight / Kilogram	0.048
EAN	7316576649691
Product Group	B00308
Enclosure	Open
Flush Ground	No
Rolling Element	Ball Bearing
Number of Rows of Balls	Single Row
Precision Class	ABEC 3 ISO P6
Maximum Capacity / Filling Slot	No
Snap Ring	No
Cage Material	Polymer
Contact Angle	40 Degree
Internal Clearance	C0-Medium
Number of Bearings	1 (Single)
Inch - Metric	Metric
Long Description	15MM Bore; 35MM Outside Diameter; 11MM



NTNY BEARING LTD

	Width; Open; No Flush Ground; Ball Bearing; Single Row of Balls; ABEC 3 ISO P6; No Filling Slot; No Snap Ring
Category	Angular Contact Ball Bearing
UNSPSC	31171531
Harmonized Tariff Code	8482.10.50.28
Noun	Bearing
Keyword String	Angular Contact
Manufacturer URL	http://www.skf.com
Manufacturer Item Number	7202 BEP
Weight / LBS	0.099
Width	0.433 Inch 11 Millimeter
Bore	0.591 Inch 15 Millimeter
Outside Diameter	1.378 Inch 35 Millimeter
bore diameter:	15 mm
radial static load capacity:	4.4 kN
outside diameter:	35 mm
cage material:	Nylon
overall width:	11 mm
outer ring width:	11 mm
contact angle:	40 °
maximum rpm:	24000 RPM
row type & fill slot:	Single-Row Non-Fill Slot
finish/coating:	Uncoated
internal clearance:	C0
precision rating:	ABEC 3 (ISO Class 6)
closure type:	Open
fillet radius:	0.6 mm
radial dynamic load capacity:	8.32 kN
series:	72



NTNY BEARING LTD

d_1	22.7 mm
d_2	18.93 mm
D_1	27.8 mm
$r_{1,2}$ min.	0.6 mm
$r_{3,4}$ min.	0.3 mm
d_a min.	19.2 mm
D_a max.	30.8 mm
D_b max.	32.6 mm
r_a max.	0.6 mm
r_b max.	0.3 mm
Basic dynamic load rating C	8.32 kN
Basic static load rating C_0	4.4 kN
Fatigue load limit P_u	0.183 kN
Calculation factor A	0.000383
Calculation factor k_r	0.095
Calculation factor e	1.14
Calculation factor X	0.35
Calculation factor Y_0	0.26
Calculation factor Y_2	0.57
Calculation factor X	0.57
Calculation factor Y_0	0.52
Calculation factor Y_1	0.55
Calculation factor Y_2	0.93
Mass bearing	0.045 kg